



tesapack[®] Eco & Strong



Product Information

BNR 58154, 58156, 58226, 58155, 58153, 58227

Product Description

tesapack[®] eco & strong is a more sustainable packaging tape made from 100% recycled plastic. It is free from PVC and solvents

Product Features

- Strong PP backing made from 100% recycled plastic
- Core made from 100% recycled cardboard
- Label made from paper
- Solvent-free adhesive with high UV-resistance
- High sealing security
- Even, low noise unwinding
- Suitable for use with all available tesapack[®] hand dispensers
- The recycled content has been approved by the independent certification organisation DIN CERTCO belonging to the TÜV Rheinland (German technical control board).

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Product Construction

- | | | | |
|--------------------|---------------------|-------------------|-------|
| • Backing | BOPP | • Total thickness | 57 µm |
| • Type of adhesive | water-based acrylic | | |

Properties/Performance Values

- | | | | |
|--------------------------|--------------------|-----------------------------|-----------|
| • Elongation at break | 80 % | • Residue-free removability | no |
| • Tensile strength | 40 N/cm | • Reusable | no |
| • Adhesive strength | High adhesion | • Roll width max | 50 mm |
| • Ageing resistance (UV) | yes | • Serrated blade | _NULL |
| • Applicationfield | Office, Home | • Solvent free | yes |
| • Batteries included | no | • Spare part service | no |
| • Batteries required | no | • Suitable surfaces | Cardboard |
| • Hand tearability | no | • Tear resistance | yes |
| • Humidity resistance | no | • Tensibility | 80 % |
| • Low noise unwinding | yes | • Tension control | _NULL |
| • Material | PP (polypropylene) | • Unwind force | 3.7 N/cm |
| • Max roll length | 66 m | • Writable | no |

For latest information on this product please visit <http://l.tesa.com/?cp=NaN>



tesapack[®] Eco & Strong

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit <http://l.tesa.com/?cp=NaN>